



Caiman CSP 4ft Twin

CCT Colour Switchable

Features

| | |
|------------------------|--------------------|
| IK Rating | IK08 |
| IP Rating | IP65 |
| CSP Switchable | Switchable CCT |
| Sensor Option | PIR with accessory |
| Dimmable Option | No |
| LED Lifetime | L70 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM4 |
| Emergency Option | Yes, Self-Test |

Installation information

| | |
|---------------------------|-----------------------|
| Install Connector Type | Loop in / Loop out |
| Inrush Current | 30A 0.3ms |
| Construction Material | Anti-UV Polycarbonate |
| Weight | 2Kg (EM: 2.4Kg) |
| Ambient Temperature Range | -20°C - 35°C |
| SELV | Yes |
| UK Building Regulations | Part P |
| Electric Class (1, 2, 3) | 1 |

Photometrics @ 25°C

| Product code | Finish | Feature l | W | Colour | Beam | lm | lm/W | lx @ 1m | EM |
|--------------|--------------|-----------|-----|--------|------|------|------|---------|----|
| AC4TN | Grey RAL7005 | Standard | 36W | 3000K | 120° | 4140 | 115 | 1189 | - |
| AC4TN | Grey RAL7005 | Standard | 36W | 4000K | 120° | 4680 | 130 | 1345 | - |
| AC4TN | Grey RAL7005 | Standard | 36W | 6500K | 120° | 4500 | 125 | 1293 | - |

Wiring information

| | |
|------------------------------|---|
| Cable Required for Connector | H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm ² |
| Type of Wiring Required | Parallel |

Accessories

| | | |
|-------------|--|-----------------|
| AC4TCLIP316 | Coastal application kit | Sold Separately |
| ACTBESA | BESA mounting kit (indoor only) | Sold Separately |
| EMBOLTMOPEN | 3 hour emergency conversion pack, open area, manual test | Sold Separately |
| EMBOLTMCOR | 3 hour emergency conversion pack, corridor area, manual test | Sold Separately |
| PIRBOLT | PIR on/off daylight Sensor | Sold Separately |



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years, 2 years on battery, 2 years on-site

Features & benefits

CCT switchable between 3000K, 4000K & 6500K

Grade 316 Coastal protection kit available

BESA mounting kit available

IP65 for the highest level of dust protection and able to withstand jets of water from any direction

304 stainless steel clips for high corrosion resistance and anti-tamper screws for vandal proofing

IK08 for robust impact protection

Unique gear tray slots that allow us to easily integrate third party control gear for your project. Just ask.

Extended mounting sliders to help make refurbishment easier

Safety tether cable to gear tray enables fast installation

Compression cable gland included in fixings kit
Light source energy efficiency:



Beam angle: 120°

