



# Arc

Wallpack suitable for 3m (10W) or 4m (17W) mounting height

## Features

IK Rating	IK10
IP Rating	IP66
CSP Switchable	Switchable CCT
Sensor Option	PC Dusk to Dawn
Dimmable Option	No
LED Lifetime	L70 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes

## Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
UK Bathroom Zone	2
Inrush Current	16A 0.2ms
Construction Material	ADC12 Aluminium alloy, uv-resistant polycarbonate lens, stainless steel 304 screws
Weight	2.6kg
Ambient Temperature Range	-30°C - 50°C
Electric Class (1, 2, 3)	1

## Photometrics @ 25°C

Product code	Finish	Feature I	W	Colour	Beam	lm	lm/W	lx @ 1m	EM
ARA1N	Anthracite grey RAL7016	Standard	10W	3000K	98°x114°	1550	155	445	-
ARA1N	Anthracite grey RAL7016	Standard	10W	4000K	98°x114°	1650	165	474	-
ARA1N	Anthracite grey RAL7016	Standard	10W	5000K	98°x114°	1600	160	459	-
ARA1NE	Anthracite grey RAL7016	Emergency	10W	3000K	98°x114°	1550	155	445	300
ARA1NE	Anthracite grey RAL7016	Emergency	10W	4000K	98°x114°	1650	165	474	300
ARA1NE	Anthracite grey RAL7016	Emergency	10W	5000K	98°x114°	1600	160	459	300
ARA2N	Anthracite grey RAL7016	Standard	17W	3000K	98°x114°	2600	153	746	-
ARA2N	Anthracite grey RAL7016	Standard	17W	4000K	98°x114°	2750	162	789	-
ARA2N	Anthracite grey RAL7016	Standard	17W	5000K	98°x114°	2700	159	775	-
ARA2NE	Anthracite grey RAL7016	Emergency	17W	3000K	98°x114°	2600	153	746	300
ARA2NE	Anthracite grey RAL7016	Emergency	17W	4000K	98°x114°	2750	162	789	300
ARA2NE	Anthracite grey RAL7016	Emergency	17W	5000K	98°x114°	2700	159	775	300

## Wiring information

Cable / Flying Lead	No flying leads are required; a loop-in, loop-out terminal is supplied.
Type of Wiring Required	Parallel

## Accessories

AREMGKIT	Arc Emergency Spare Kit	Sold Separately
----------	-------------------------	-----------------



01604 495 151  
collingwoodlighting.com

- collingwoodled  
 /collingwoodlighting  
 collingwoodlighting

## Guarantee

5 years

## Features & benefits

CCT switchable between 3000K, 4000K & 5000K

Up to 165lm/W efficacy

Integral photocell as standard

Designed to illuminate a pathway efficiently and safely, whilst preserving the habitat

Highly energy efficient with up to 165 luminaire lumens per watt for low total cost over luminaire's lifetime

Anti-glare optical control designed to reduce upward sky glow

Set to 3000K as standard (CCT switchable) to minimise low blue light content

Integral photocell to switch the light ON at dusk and OFF at dawn

Slim 97mm profile integrates discreetly to the building architecture

Removeable backplate to aid fast installation

Light source energy efficiency:



Beam angle: 98°x114°

