



BOL100 Midi Post Light

Straight to mains IP54, 610lm post light

Features

IK Rating	IK04
IP Rating	IP54
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

Installation information

UK Bathroom Zone	2
Inrush Current	20A
Construction Material	Aluminium / PVC
Weight	1.2kg
Ambient Temperature Range	40°C
SELV	SELV
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
BOL100X30	Black RAL9011	11W	3000K	360°	610	55	92

Wiring information

Cable Required for Connector	3x 1.0mm²
Type of Wiring Required	Parallel

LED driver

N/A (Integrated SLEV driver)	220-240V	Yes	No	2	-	-
------------------------------	----------	-----	----	---	---	---

Accessories

JB5	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
-----	------------------------------------------------------------	-----------------



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years


Features & benefits

- 11W
- IP54 ideal for walk ways and step lighting
- Benefiting from light all round with a 360° beam angle
- Straight to mains screw terminals
- Ideal for residential landscape projects, such as lighting low level shrubs
- Ideal to light up car parking spaces and driveways
- High lumen output of 610lm
- Great for soft illumination onto stone paths

Light source
energy efficiency:



Beam angle: 360°



Ø80mm

