

01604 495 151  
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

## H2 Lite

TRIAC Dimmable, fire-rated downlight with integrated bezel & Easy-fit connector

### Features

IP Rating	IP65 (from below) IP20 (from above)
CSP Switchable	Single CCT
UGR	22
Sensor Option	Smart Microwave
Dimmable Option	Yes (Mains)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	No

### Installation information

Install Connector Type	Easy-fit connector
Insulation Coverable	Rolled and blown insulation
Cut Out Size	64-72
UK Bathroom Zone	1
Inrush Current	1.3A 0.23ms
Construction Material	Mild steel / VO rated plastic
Thickness of Recessed Surface	40 mm
Weight	180g
Ambient Temperature Range	40°C
SELV	SELV
UK Building Regulations	Part B, C, E, P & L
Ceiling Joist Approvals	Solid timber, I-Joist and Metal Web
Electric Class (1, 2, 3)	2

### Guarantee

10 years

### Features & benefits

Patented Easy-fit connector for first & second fix

Shallow depth 46mm

Insulation coverable

With approximately 5 million units supplied to a wide range of customers, H2 Lite has a proven history of excellent performance, fast installation and lifetime you can trust

Unique product design with a new shallow depth to enable use in the smallest of ceiling voids

TRIAC mains dimmable, works with leading & trailing edge dimmers

Optimised design with no waste, minimizing the use of materials and impact on the planet

FSC certificated packaging ensure minimal waste

### Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
DLT388BS5540	Brushed steel	4.3W	4000K	55°	490	114	440
DLT388BS5530	Brushed steel	4.3W	3000K	55°	460	107	413
DLT388MW5540	Matt white	4.3W	4000K	55°	490	114	440
DLT388MW5530	Matt white	4.3W	3000K	55°	460	107	413
DLT388BLK5540	Matt black	4.3W	4000K	55°	490	114	440
DLT388BLK5530	Matt black	4.3W	3000K	55°	460	107	413

Product not suitable for exterior use, please use H2 Pro Extreme.

### Wiring information



Cable / Flying Lead	0.15m
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm <sup>2</sup> ) or 3-core cable (R02V 3x1.5mm <sup>2</sup> )
Type of Wiring Required	Parallel

### LED driver

N/A (integrated SELV driver)	220-240V	Yes	Yes (mains)	1 (Ceiling only)	N/A	N/A
------------------------------	----------	-----	-------------	------------------	-----	-----



Beam angle: 55°



## Accessories

<b>DLCONVERT70</b>	Converter plate	Sold Separately
<b>DM298GRID</b>	LED mains grid dimmer	Sold Separately
<b>DM298FP</b>	Faceplate dimmer	Sold Separately
<b>DLCVT110</b>	Converter Plate	Sold Separately



collingwood

01604 495 151  
[collingwoodlighting.com](http://collingwoodlighting.com)

 [collingwoodled](https://www.instagram.com/collingwoodled)

 [/collingwoodlighting](https://www.facebook.com/collingwoodlighting)

 [collingwoodlighting](https://www.linkedin.com/company/collingwoodlighting)

---

## H2 Lite

Updated for 2023, our bestselling H2 LED Downlight. With approximately 5 million units supplied, to a wide range of customers, and projects, the H2 Lite offers quality lighting, fast fitting and lifetime you can trust. Now even more efficient, at 114Lm/W, and with a reduced the depth for ease of installation, even in the smallest of ceiling voids. Our patented Easy-Fit connector makes for a quick and easy installation. Supplied with integrated bezel, in Brushed Steel, Matt White, and stylish New Matt Black, in 3000K or 4000K to compliment your space. The H2, TRIAC Dimmable, fire-rated downlight, now comes with a NEW 10 YEARS Warranty, and an extended lifetime of 70,000 hours.