



Domino White

Ultra-low Glare 600x600 Architectural Panel

Features

IK Rating	IK08
IP Rating	IP40
CSP Switchable	Single CCT
UGR	16
Sensor Option	On Request
Dimmable Option	Yes (DALI-2, 0-10V, PUSH-DIM)
LED Lifetime	L90 51,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Emergency Option	Yes, using converter

Installation information

Install Connector Type	2 part first fit connector
Insulation Coverable	Luminaire: Rolled and blown insulation Driver: no
UK Bathroom Zone	2
Inrush Current	28A <50ms
Construction Material	Steel Housing, Polycarbonate Lens
Weight	3.8kg
Ambient Temperature Range	-20°C - 40°C
SELV	Yes
UK Building Regulations	Part P & L
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	W	Colour	Beam	lm	lm/W	EM
DMW66X4K	White RAL9003	Dimmable	Use driver PS6501100MA	27W	4000K	75°	4350	161	See Accessories
DMW66X4K	White RAL9003	Dimmable	Use driver PS6501100MA	27W		75°			See Accessories
DMW66N4K	White RAL9003	Non-Dimmable	Driver included with lumen output switch	22W	4000K	75°	3550	161	See Accessories
DMW66N4K	White RAL9003	Non-Dimmable	Driver included with lumen output switch	24W	4000K	75°	3850	160	See Accessories

Energy rating is a reflection of the LED light source.

Wiring information

Cable / Flying Lead	0.75-1.5mm ²
Type of Wiring Required	Parallel

Accessories

PS6501100MA	one4all driver DALI-2, Push-dim, 0-10V, 10V PWM	Sold Separately
EUP30TIHMC0	Driver, 30W Panel, TRIAC Mains Dim	Sold Separately
DRV3001050	42W CC Driver, IP20, 300-1050mA, Class II SELV	Sold Separately
LEDEPI0	Emergency converter, Self-test, 220lm	Sold Separately
LEDEP09DA	Emergency converter, DALI Addressable, 220lm	Sold Separately
EMRWMAN	Salvus Route White, Man-Test, 120(O) or 130(C) lm	Sold Separately
EMRWST	Salvus Route White, Self Test, 120lm(O) or 130lm(C)	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

5 years (product), 3 years (emg battery), 2 years (on-site)

Features & benefits

UGR16 for office, classroom and retail application

Wattage switchable between 22W, 24W, 25W & 27W

Energy efficient up to 164 lm/W

Perfect for office, classroom and retail application

Differentiate the look of your space with a high-quality aesthetic

51,000 hours L90 lifetime

High impact rating of IK08


Security cable supplied

RG0 (Risk Exempt) Photo-biological Risk

Light source energy efficiency:



Beam angle: 75°



600mm

18mm

