



Salvus Emergency Bulkhead

145lm, emergency bulkhead, 18m viewing distance

Features

IK Rating	IK07
IP Rating	IP65
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
Inrush Current	20A
Construction Material	Lens PC housing ABS
Weight	0.65Kg
Ambient Temperature Range	45°C
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Feature I	Feature II	Feature III	W	Colour	Beam	lm
EMBHI45M	Maintained & Non-Maintained	View Dist 18m	Manual Test	3.0W	6500K	120°	145
EMBHI45S	Maintained & Non-Maintained	View Dist 18m	Self Test	3.0W	6500K	120°	145

Wiring information

Cable / Flying Lead	0.5 to 1.0mm ²
Type of Wiring Required	Parallel

Accessories

N/A	No accessories are required
-----	-----------------------------



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

2 years

Features & benefits

- LiFePO4 battery available
- Self-test or Manual test available
- IP65 suitable for outdoor environments
- By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage
- Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points
- Lens is rugged and made of polycarbonate
- Viewing distance of 18m
- Complying with ISO 3864-1, and proud members of the ICEL
- Ideal for open areas, escape routes, for general illumination or as an exit sign
- Adhesive legend is supplied and divided in five parts

Beam angle: 120°

