



Salvus Emergency Exit Blade

50lm, emergency exit blade, 30m viewing distance

Features

IK Rating	IK08
IP Rating	IP20
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
Inrush Current	10.3A 100s
Construction Material	Lens PC housing PC
Weight	0.9Kg
Ambient Temperature Range	45°C
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Feature I	Feature II	Feature III	W	Colour	Beam	lm
EMBL30M	Maintained	View Dist 30m	Manual Test	4.0W	6500K	120°	50
EMBL30S	Maintained	View Dist 30m	Self Test	4.0W	6500K	120°	50

Wiring information

Cable / Flying Lead	Screwless terminals, up to 0.75mm ²
Type of Wiring Required	Parallel

Accessories

EMBLUP	Pictogram Arrow UP.	Sold Separately
EMBLDO	Pictogram Arrow DOWN.	Sold Separately
EMBLRI	Pictogram Arrow RIGHT.	Sold Separately
EMBLLE	Pictogram Arrow LEFT.	Sold Separately
EMBLSK	Suspension Kit (2x 1m cable + fixings)	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

3 years

Features & benefits

- LiFePO4 battery available
- Self-test or Manual test available
- Auxiliary floor illumination to light areas under fitting
- Maintained, so it can be turned on/off when the mains is on
- Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points
- Housing is rugged and made of polycarbonate
- 30m viewing distance allowing it to be assembled in different room dimensions
- Complying with ISO 3864-1, and proud members of the ICEL

