



Salvus Emergency Exit Blade Accessories

Emergency exit blade label

Features

IP Rating	IP67
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	80
UK Bathroom Zone	2
Inrush Current	9A 0.8ms
Construction Material	PVC
Weight	1000g
Ambient Temperature Range	35°C

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

USE WITH

EMBL30M	Salvus Emergency Exit Blade	Sold Separately
EMBL30S	Salvus Emergency Exit Blade	Sold Separately
WC 5-9	Quick release waterproof joint	Sold Separately

PRODUCT CODES

	Description	Characteristic 1	Characteristic 2	Characteristic 3
EMBLUP	Emergency Exit Blade Label Up	Arrow Up	Used with Exit Blade	Viewing Distance 30m
EMBLDO	Emergency Exit Blade Label Down	Arrow Down	Used with Exit Blade	Viewing Distance 30m
EMBLLE	Emergency Exit Blade Label Left	Arrow Left	Used with Exit Blade	Viewing Distance 30m
EMBLRI	Emergency Exit Blade Label Right	Arrow Right	Used with Exit Blade	Viewing Distance 30m



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

3 Year Extended Warranty

Features & benefits

Comes as an PVC label for ease of installation

Instantly and unmistakably indicate the exit routes

Complying with ISO 3864-1, and proud members of the ICEL

