



# Salvus Emergency Exit Blade Accessories

Emergency exit blade label

### Features

|           |      |
|-----------|------|
| IP Rating | IP67 |
|-----------|------|

### Installation information

|                       |          |
|-----------------------|----------|
| Cut Out Size          | 80       |
| UK Bathroom Zone      | 2        |
| Inrush Current        | 9A 0.8ms |
| Construction Material | PVC      |
| Weight                | 1000g    |

### USE WITH

|         |                                |                 |
|---------|--------------------------------|-----------------|
| EMBL30M | Salvus Emergency Exit Blade    | Sold Separately |
| EMBL30S | Salvus Emergency Exit Blade    | Sold Separately |
| WC 5-9  | Quick release waterproof joint | Sold Separately |

### PRODUCT CODES

|        | Description                      | Characteristic 1 | Characteristic 2     | Characteristic 3     |
|--------|----------------------------------|------------------|----------------------|----------------------|
| EMBLUP | Emergency Exit Blade Label Up    | Arrow Up         | Used with Exit Blade | Viewing Distance 30m |
| EMBLDO | Emergency Exit Blade Label Down  | Arrow Down       | Used with Exit Blade | Viewing Distance 30m |
| EMBLLE | Emergency Exit Blade Label Left  | Arrow Left       | Used with Exit Blade | Viewing Distance 30m |
| EMBLRI | Emergency Exit Blade Label Right | Arrow Right      | Used with Exit Blade | Viewing Distance 30m |



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

### Guarantee

3 Year Extended Warranty

### Features & benefits

Comes as an PVC label for ease of installation

Instantly and unmistakably indicate the exit routes

Complying with ISO 3864-1, and proud members of the ICEL

