



collingwood

01604 495 151  
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

# Salvus Max

High output non-maintained emergency bulkhead

## Features

<b>IK Rating</b>	IK08
<b>IP Rating</b>	IP66
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 50,000h
<b>Colour Rendering Index</b>	CRI>80

## Installation information

<b>Install Connector Type</b>	Push-fit terminal, loop-in/loop-out
<b>Inrush Current</b>	6.8A 0.1ms
<b>Construction Material</b>	PC
<b>Weight</b>	1.47kg
<b>Ambient Temperature Range</b>	0°C - 45°C
<b>Electric Class (1, 2, 3)</b>	2

## Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	W	Colour	Beam	lm	lm/W	lx @ 1m	EM
EMBMAX	White	Wattage Switchable	Manual Test	6W   10W	6500K	135°	1000-1500	150-167	204-306lx	1000-1500lm
EMBMAXST	White	Wattage Switchable	Self Test	6W   10W	6500K	135°	1000-1500	150-167	204-306lx	1000-1500lm

## Wiring information

<b>Cable / Flying Lead</b>	0.75-4.0mm <sup>2</sup>
<b>Type of Wiring Required</b>	Parallel

## Accessories

<b>Springbok Lite</b>	Use as remote emergency solution to reduce light points required	Sold Separately
<b>Area Bay</b>	Use as remote emergency solution to reduce light points required	Sold Separately
<b>Caiman</b>	Use as remote emergency solution to reduce light points required	Sold Separately
<b>Borealis</b>	Use as remote emergency solution to reduce light points required	Sold Separately

## Guarantee

4 years on electronics, 2 years on battery

## Features & benefits

- High efficacy of 167lm/W
- Wattage Switchable between 6W & 10W
- IP66 suitable for warehouse all applications
- 1500lm output
- 15 metres mounting height, provides 1 lux (escape route) at floor level when using 29 metre spacings
- 25 metres mounting height, provides 0.5 (anti-panic) lux at floor level when using 40 metre spacings
- Lithium iron phosphate (LiFePO4) battery technology for long lifetime and fast charge times
- Captive screws for easy installation

## Beam angle: 135°

