



Salvus Max

High output non-maintained emergency bulkhead

Features

IK Rating	IK08
IP Rating	IP66
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80

Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
Inrush Current	6.8A 0.1ms
Construction Material	PC
Weight	1.47kg
Ambient Temperature Range	0°C - 45°C
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	W	Colour	Beam	lm	lm/W	lx @ 1m	EM
EMBMAX	White	Wattage Switchable	Manual Test	6W 10W	6500K	135°	1000-1500	150-167	204-306lx	1000-1500lm
EMBMAXST	White	Wattage Switchable	Self Test	6W 10W	6500K	135°	1000-1500	150-167	204-306lx	1000-1500lm

Wiring information

Cable / Flying Lead	0.75-4.0mm ²
Type of Wiring Required	Parallel

Accessories

Area Bay	Use as remote emergency solution to reduce light points required	Sold Separately
Caiman	Use as remote emergency solution to reduce light points required	Sold Separately
Borealis	Use as remote emergency solution to reduce light points required	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

4 years on electronics, 2 years on battery

Features & benefits

- High efficacy of 167lm/W
- Wattage Switchable between 6W & 10W
- IP66 suitable for warehouse all applications
- 1500lm output
- 15 metres mounting height, provides 1 lux (escape route) at floor level when using 29 metre spacings
- 25 metres mounting height, provides 0.5 (anti-panic) lux at floor level when using 40 metre spacings
- Lithium iron phosphate (LiFePO4) battery technology for long lifetime and fast charge times
- Captive screws for easy installation

Beam angle: 135°

