



Bolt-On Emergency

3 hour emergency conversion pack, corridor area, self-test

Features

IP Rating	IP65
Emergency Option	Emergency Version

Installation information

Install Connector Type	Flying lead
Inrush Current	2A 2.6ms
Construction Material	PC
Weight	219g
Ambient Temperature Range	0°C to +45°C
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	Feature III	W	Colour	lm	lx @ 1m
EMBOLTSCOR	White RAL9016	Non-Maintained	Corridor Lens	Self Test	2.5W Max	6000K	200	51
EMBOLTSOPEN	White RAL9016	Non-Maintained	Open Area Lens	Self Test	2.5W Max	6000K	200	51
EMBOLTMCOR	White RAL9016	Non-Maintained	Corridor Lens	Manual Test	2.5W Max	6000K	200	51
EMBOLTMOPEN	White RAL9016	Non-Maintained	Open Area Lens	Manual Test	2.5W Max	6000K	200	51

Wiring information

Cable / Flying Lead	1.4m (2x 0.75mm ²)
Type of Wiring Required	Parallel

Accessories

Borealis Batten	All variants	Sold Separately
Caiman Anti Corrosive	All variants	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

4 years guarantee of the electronics
2 years guarantee of the battery

Features & benefits

- Self or Manual Test Options
- M20 interface for easy installation
- Lithium iron phosphate battery (LiFePO4)
- Compatible with:
 - BOREALIS Batten
 - CAIMAN Anti-Corrosive
 - LENTUS Lowbay
- Suitable for use at heights of 2.5 to 6.0 metres
- Fast 4-minute conversion time

Beam angle:

