



Bolt-On Emergency

3 hour emergency conversion pack, corridor area, self-test

Features

IK Rating	IK07
IP Rating	IP65
Sensor Option	No
Colour Rendering Index	CRI>70
Emergency Option	Emergency Version

Installation information

Install Connector Type	Flying lead
UK Bathroom Zone	N/A
Inrush Current	2A 2.6ms
Construction Material	PC
Weight	219g
Electric Class (1, 2, 3)	2

Wiring information

Cable / Flying Lead	1.4m (2x 0.75mm ²)
Type of Wiring Required	Parallel

USE WITH

Borealis Batten	All variants	Sold Separately
Caiman Anti Corrosive	All variants	Sold Separately
Lentus Lowbay	All variants	Sold Separately

PRODUCT CODES

	Colour / Finish	Description	Characteristic 1	Characteristic 2	Characteristic 3
EMBOLTS COR	White RAL9016	3 hour emergency conversion pack, corridor area, self-test	Non-Maintained	Corridor Lens	Self Test
EMBOLTS OPEN	White RAL9016	3 hour emergency conversion pack, open area, self-test	Non-Maintained	Open Area Lens	Self Test
EMBOLT MCOR	White RAL9016	3 hour emergency conversion pack, corridor area, manual test	Non-Maintained	Corridor Lens	Manual Test
EMBOLT MOPEN	White RAL9016	3 hour emergency conversion pack, open area, manual test	Non-Maintained	Open Area Lens	Manual Test



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

4 years guarantee of the electronics
2 years guarantee of the battery

Features & benefits

- Compatible with:
 - BOREALIS Batten
 - CAIMAN Anti-Corrosive
 - LENTUS Lowbay
- Suitable for use at heights of 2.5 to 6.0 metres
- Fast 4-minute conversion time
- M20 interface for easy installation

Beam angles: 155° x 68° 145°

