



# Bolt-On Emergency

3 hour emergency conversion pack, corridor area, self-test

## Features

IK Rating	IK07
IP Rating	IP65
Sensor Option	No
Colour Rendering Index	CRI>70
Emergency Option	Emergency Version

## Installation information

Install Connector Type	Flying lead
UK Bathroom Zone	N/A
Inrush Current	2A 2.6ms
Construction Material	PC
Weight	219g
Electric Class (1, 2, 3)	2

## Wiring information

Cable / Flying Lead	1.4m (2x 0.75mm <sup>2</sup> )
Type of Wiring Required	Parallel

## USE WITH

Borealis Batten	All variants	Sold Separately
Caiman Anti Corrosive	All variants	Sold Separately
Lentus Lowbay	All variants	Sold Separately

## PRODUCT CODES

	Colour / Finish	Description	Characteristic 1	Characteristic 2	Characteristic 3
EMBOLTS COR	White RAL9016	3 hour emergency conversion pack, corridor area, self-test	Non-Maintained	Corridor Lens	Self Test
EMBOLTS OPEN	White RAL9016	3 hour emergency conversion pack, open area, self-test	Non-Maintained	Open Area Lens	Self Test
EMBOLT MCOR	White RAL9016	3 hour emergency conversion pack, corridor area, manual test	Non-Maintained	Corridor Lens	Manual Test
EMBOLT MOPEN	White RAL9016	3 hour emergency conversion pack, open area, manual test	Non-Maintained	Open Area Lens	Manual Test



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

4 years guarantee of the electronics  
2 years guarantee of the battery

## Features & benefits

Compatible with:  
BOREALIS Batten  
CAIMAN Anti-Corrosive  
LENTUS Lowbay  
Suitable for use at heights of 2.5 to 6.0 metres  
Fast 4-minute conversion time  
M20 interface for easy installation

Beam angles: 155° x 68° 145°

