



Salvus Emergency Exit Box

47lm, emergency exit box, 35m viewing distance

Features

IK Rating	IK08
IP Rating	IP20
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
Inrush Current	12A 56s
Construction Material	Lens PC housing PC
Weight	0.6Kg
Ambient Temperature Range	0°C - 45°C
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Feature I	Feature II	Feature III	W	Colour	Beam	lm
EMBX35M	Maintained & Non-Maintained	View Dist 35m	Manual Test	3.5W	6500K	N/A	47
EMBX35S	Maintained	View Dist 35m	Self Test	3.5W	6500K	N/A	47

Wiring information

Cable / Flying Lead	0.5 to 1.0mm ²
Type of Wiring Required	Parallel

Accessories

EMBXUP	Pictogram Arrow UP.	Sold Separately
EMBXDO	Pictogram Arrow DOWN.	Sold Separately
EMBXRI	Pictogram Arrow RIGHT.	Sold Separately
EMBXLE	Pictogram Arrow LEFT.	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

Manual-test: 2 yearsSelf-test: 3 years

Features & benefits

- LiFeP04 battery available
- Self-test or Manual test available
- Auxiliary floor illumination to light areas under fitting
- By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage
- NiCd is a well-proven and widely used technology
- Housing is rugged and made of polycarbonate
- 35m viewing distance allowing it to be assembled in many different room dimensions
- Complying with ISO 3864-1, and proud members of the ICEL

