



# Salvus Emergency Exit Box

47lm, emergency exit box, 35m viewing distance

## Features

IK Rating	IK08
IP Rating	IP20
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

## Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
Inrush Current	12A 56s
Construction Material	Lens PC housing PC
Weight	0.6Kg
Ambient Temperature Range	0°C - 45°C
Electric Class (1, 2, 3)	2

## Photometrics @ 25°C

Product code	Feature I	Feature II	Feature III	W	Colour	Beam	lm
EMBX35M	Maintained & Non-Maintained	View Dist 35m	Manual Test	3.5W	6500K	N/A	47
EMBX35S	Maintained	View Dist 35m	Self Test	3.5W	6500K	N/A	47

## Wiring information

Cable / Flying Lead	0.5 to 1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

## Accessories

EMBXUP	Pictogram Arrow UP.	Sold Separately
EMBXDO	Pictogram Arrow DOWN.	Sold Separately
EMBXRI	Pictogram Arrow RIGHT.	Sold Separately
EMBXLE	Pictogram Arrow LEFT.	Sold Separately



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

Manual-test: 2 yearsSelf-test: 3 years

## Features & benefits

- LiFeP04 battery available
- Self-test or Manual test available
- Auxiliary floor illumination to light areas under fitting
- By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage
- NiCd is a well-proven and widely used technology
- Housing is rugged and made of polycarbonate
- 35m viewing distance allowing it to be assembled in many different room dimensions
- Complying with ISO 3864-1, and proud members of the ICEL

