



Salvus Emergency Twin Spot

400lm, self test emergency twin spot

Features

IK Rating	IK08
IP Rating	IP65
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

Installation information

Install Connector Type	Push-fit terminal, loop-in/loop-out
Inrush Current	10.8A 84s
Construction Material	Lens PC housing PC
Weight	1Kg
Ambient Temperature Range	0°C - 45°C
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Feature I	Feature III	W	Colour	Beam	lm
EMTW400S	Non-Maintained	Self Test	4.8W	6500K	105°	400

Wiring information

Cable / Flying Lead	0.5 to 1.0mm ²
Type of Wiring Required	Parallel

Accessories

N/A (No Accessories required)



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

3 years

Features & benefits

- LiFeP04 battery available
- Self-test available
- IP65 suitable for outdoor environments
- Adjustable LED heads allow beam aiming
- A rugged robust polycarbonate lens and housing
- Charging Time = 24h
- IEC reference standard - EN 60598-2-22, EN 62034

Beam angle: 105°

