



# Fountain

Water feature light

## Features

IK Rating	IK08
IP Rating	IP68
CSP Switchable	Single CCT
Walk Over / Drive Over	Walk over (Stainless Steel Only)
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

## Installation information

Install Connector Type	Flying lead
Cut Out Size	167
UK Bathroom Zone	0, 1 (with dimming)
Inrush Current	N/A
Construction Material	316 Stainless Steel
Weight	2.58kg
Ambient Temperature Range	-25°C - 40°C
SELV	Yes
Electric Class (1, 2, 3)	3

## Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
FOUX167N30	Stainless steel 316	25W	3000K	35°	1700	68	4057

Energy rating is a reflection of the LED light source.

## Wiring information

Cable / Flying Lead	Pre-wired 5.0M H05RN-F, 2x1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

## LED drivers

PSIP15024	220-240V	Yes	Yes (with PDCINT 1-10V)	N/A	1	6
LSD12024	220-240V	Yes	No	Outside zones	1	4
PSIP25024	220-240V	Yes	No	0	1	10

## Accessories

JB5	Gel filled waterproof connector	Sold Separately
-----	---------------------------------	-----------------



01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

5 years

## Features & benefits

- IP68 suitable for full submersion into water
- IK08 for protection against high impact
- Suitable for coastal C5 and high acid and alkali environment
- 316 Stainless steel housing and titanium cover provides outstanding corrosion resistance
- Clear but strong 8mm tempered glass cover provides high efficiency and clear colour accuracy
- TRIAC mains dimmable as standard with RGBW option
- Pre-wired with 5 metres of cable to aid the installer
- To be installed under water to prevent over-heating
- 1 1/2" BSP thread enables installation onto fabricated pipework
- RGBW version available

