



01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

Fountain

Water feature light

Features

IK Rating	IK08
IP Rating	IP68
CSP Switchable	Single CCT
Walk Over / Drive Over	Walk over
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Install Connector Type	Flying lead
Cut Out Size	167
UK Bathroom Zone	0, 1 (with dimming)
Inrush Current	N/A
Construction Material	316 Stainless Steel
Weight	2.58kg
Ambient Temperature Range	-25°C - 40°C
SELV	Yes
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
FOUX167N30	Stainless steel 316	25W	3000K	35°	1700	68	4057

Wiring information

Cable / Flying Lead	Pre-wired 5.0M H05RN-F, 2x1.0mm ²
Type of Wiring Required	Parallel

LED drivers

PS5024	220-240V	Yes	No	0	1	2
LSD12024	220-240V	Yes	No	0	1	4
PSIP25024	220-240V	Yes	No	0	1	10

Accessories

JB5	Gel filled waterproof connector	Sold Separately
-----	---------------------------------	-----------------

Guarantee

5 years

Features & benefits

IP68 suitable for full submersion into water

IK08 for protection against high impact

Suitable for coastal C5 and high acid and alkali environment

316 Stainless steel housing and titanium cover provides outstanding corrosion resistance

Clear but strong 8mm tempered glass cover provides high efficiency and clear colour accuracy

TRIAC mains dimmable as standard with RGBW option

Pre-wired with 5 metres of cable to aid the installer

To be installed under water to prevent over-heating

1 1/2" BSP thread enables installation onto fabricated pipework

RGBW version available

Light source energy efficiency: 

Beam angle: 35°

