



GL016 F AB

1W, 95lm ground light

Features

IK Rating	IK09
IP Rating	IP68
CSP Switchable	Single CCT
Walk Over / Drive Over	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	50
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Brass
Weight	400g
Ambient Temperature Range	50°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL016 F AB NW	Brass	1W (350mA)	4000K	26°	95	95	267
GL016 F AB NW	Brass	2W (700mA)	4000K	26°	140	70	393
GL016 F AB WW	Brass	1W (350mA)	3000K	26°	75	75	210
GL016 F AB WW	Brass	2W (700mA)	3000K	26°	135	68	379
GL016 F AB 27	Brass	1W (350mA)	2700K	26°	70	70	196
GL016 F AB 27	Brass	2W (700mA)	2700K	26°	120	60	337

Energy rating is a reflection of the LED light source.

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/50	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

7 years

Features & benefits

1W at 350mA or 2W at 700mA

Solid brass with antique effect for low glare

Low voltage ground light

Robust cable for outdoor use

Shallow depth for easy installation

Coastal protected

