



GL018 C

0.5W, 31mm mini round marker ground light

Features

IK Rating	IK07
IP Rating	IP68
CSP Switchable	Single CCT
Walk Over / Drive Over	Walk over
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	28
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	300g
Ambient Temperature Range	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL018 C NW	Stainless steel	0.4W	4000K	120°	4	10	1
GL018 C 27	Stainless steel	0.4W	2700K	120°	4	10	1
GL018 C WW	Stainless steel	0.4W	3000K	120°	4	10	1
GL018 C BLUE	Stainless steel	0.4W	Blue	120°	0.5	1.3	0.18

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Parallel

LED drivers

PS1524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	30
PS3024B	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	60
LSD6024	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	120

Accessories

JB1 / JB5 / JB6	IP68 waterproof connectors	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled
 /collingwoodlighting
 collingwoodlighting

Guarantee

7 years

Features & benefits

0.5W at 24V DC
Frosted effect for low glare and soft lighting
Low voltage ground light
Robust cable for outdoor use
Shallow depth for easy installation
Coastal protected
Easy and quick installation with parallel wiring

Light source
energy efficiency:



Beam angle: 120°

