



## GL018 C

0.5W, 31m mini round marker ground light

### Features

<b>IK Rating</b>	IK07
<b>IP Rating</b>	IP68
<b>CSP Switchable</b>	Single CCT
<b>Walk Over / Drive Over</b>	Walk over (Stainless Steel & Antique Brass Only)
<b>LED Lifetime</b>	L70 30,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3

### Installation information

<b>Cut Out Size</b>	28
<b>UK Bathroom Zone</b>	0
<b>Inrush Current</b>	N/A
<b>Construction Material</b>	Stainless steel (316)
<b>Weight</b>	300g
<b>Ambient Temperature Range</b>	35°C
<b>SELV</b>	N/A
<b>Electric Class (1, 2, 3)</b>	3

### Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL018 C NW	Stainless steel	0.4W	4000K	120°	4	10	1
GL018 C 27	Stainless steel	0.4W	2700K	120°	4	10	1
GL018 C WW	Stainless steel	0.4W	3000K	120°	4	10	1
GL018 C BLUE	Stainless steel	0.4W	Blue	120°	0.5	1.3	0.18

Energy rating is a reflection of the LED light source.

### Wiring information

<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Parallel

### LED drivers

PS1524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	30
PS3024B	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	60
LSD6024	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	120

### Accessories

<b>JB1 / JB5 / JB6</b>	IP68 waterproof connectors	Sold Separately
<b>PDCINT1-10V</b>	1-10V dimming interface for use with 24V LED drivers	Sold Separately



01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

### Guarantee

7 years

### Features & benefits

- 0.5W at 24V DC
- Frosted effect for low glare and soft lighting
- Low voltage ground light
- Robust cable for outdoor use
- Shallow depth for easy installation
- Coastal protected
- Easy and quick installation with parallel wiring

Light source  
energy efficiency:



Beam angle: 120°

