



01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

GL019 Frosted

1W, 13lm frosted mini ground light

Features

IK Rating	IK07
IP Rating	IP68
CSP Switchable	Single CCT
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	33
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	196g
Ambient Temperature Range	50°C
Electric Class (1, 2, 3)	3

Guarantee

7 years

Features & benefits

- 1W at 350mA or 2W at 700mA
- Frosted effect for low glare and soft lighting
- Low voltage ground light
- Robust cable for outdoor use
- Shallow depth for easy installation

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL019DC0F40	Stainless steel	1W (350mA)	4000K	100°	13	13	5
GL019DC0F30	Stainless steel	1W (350mA)	3000K	100°	11	11	4
GL019DC0F27	Stainless steel	1W (350mA)	2700K	100°	10	10	4
GL019DC0FBL	Stainless steel	1W (350mA)	Blue	100°	2	2	
GL019BC0F27	Black	1W (350mA)	2700K	100°	10	10	4
GL019BC0F30	Black	1W (350mA)	3000K	100°	11	11	4
GL019BC0F40	Black	1W (350mA)	4000K	100°	13	13	5

Energy rating is a reflection of the LED light source.

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

Light source energy efficiency: 

Beam angle: 100°

