



GL019 Frosted

1W, 13lm frosted mini ground light

Features

| | |
|------------------------|-------------|
| IK Rating | IK07 |
| IP Rating | IP68 |
| CSP Switchable | Single CCT |
| Walk Over / Drive Over | Walk over |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |

Installation information

| | |
|---------------------------|-----------------------|
| Cut Out Size | 33 |
| UK Bathroom Zone | 0 |
| Inrush Current | N/A |
| Construction Material | Stainless steel (316) |
| Weight | 196g |
| Ambient Temperature Range | 50°C |
| Electric Class (1, 2, 3) | 3 |

Photometrics @ 25°C

| Product code | Finish | Colour | Beam | W | lm | lm/W | lx @ 1m | W |
|--------------|--------|--------|------|-------|----|------|---------|-------|
| | | | | 350mA | | | | 700mA |
| GL019BC0F27 | Black | 2700K | 100° | 1W | 10 | 10 | 4 | 2W |
| GL019BC0F30 | Black | 3000K | 100° | 1W | 11 | 11 | 4 | 2W |
| GL019BC0F40 | Black | 4000K | 100° | 1W | 13 | 13 | 5 | 2W |

Wiring information

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |

LED drivers

| | | | | | | |
|-------------|----------|-----|----|---|---|---|
| PLU/350 1-9 | 220-240V | Yes | No | 0 | 1 | 9 |
| PLU/700 3-9 | 220-240V | Yes | No | 0 | 3 | 9 |
| PSIP70018W | 220-240V | Yes | No | 0 | 1 | 8 |

Accessories

| | | |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | IP68 waterproof connectors | Sold Separately |
| TUBE332 | Installation tube | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 years

Features & benefits

1W at 350mA or 2W at 700mA

Frosted effect for low glare and soft lighting

Low voltage ground light

Robust cable for outdoor use

Shallow depth for easy installation

Light source
energy efficiency:



Beam angle: 100°

