



GL019 Frosted

1W, 13lm frosted mini ground light

Features

IK Rating	IK07
IP Rating	IP68
CSP Switchable	Single CCT
Walk Over / Drive Over	Walk over
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	33
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	196g
Ambient Temperature Range	50°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	Colour	Beam	W	lm	lm/W	lx @ 1m	W
				350mA				700mA
GL019BC0F27	Black	2700K	100°	1W	10	10	4	2W
GL019BC0F30	Black	3000K	100°	1W	11	11	4	2W
GL019BC0F40	Black	4000K	100°	1W	13	13	5	2W

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 years

Features & benefits

1W at 350mA or 2W at 700mA

Frosted effect for low glare and soft lighting

Low voltage ground light

Robust cable for outdoor use

Shallow depth for easy installation

Light source energy efficiency:



Beam angle: 100°

