



# GL019 Ultra low glare

1W, 78lm mini ground light

## Features

IK Rating	IK07
IP Rating	IP68
CSP Switchable	Single CCT
UGR	10
Walk Over / Drive Over	Walk over
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

## Installation information

Cut Out Size	33
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	260g
Ambient Temperature Range	50°C
Electric Class (1, 2, 3)	3

## Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL019DNBL40	Stainless steel	1W	4000K	12°	78	78	2369
GL019DMBL30	Stainless steel	1W	3000K	30°	64	64	25
GL019DNBL30	Stainless steel	1W	3000K	12°	74	74	1324
GL019DMBL27	Stainless steel	1W	2700K	30°	60	60	24
GL019DNBL27	Stainless steel	1W	2700K	12°	70	70	1292
GL019BNBL40	Black	1W	4000K	12°	78	78	2369
GL019ANBL30	Antique brass	1W	3000K	12°	74	74	1272

## Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

## LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	9
PSIP3509W	220-240V	Yes	No	0	1	8
PSMD35039	220-240V	Yes	Yes (mains)	0	3	9

## Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



01604 495 151  
collingwoodlighting.com

collingwoodled  
 /collingwoodlighting  
 collingwoodlighting

## Guarantee

7 years

## Features & benefits

1W at 350mA  
Baffled for low glare and visual comfort  
Low voltage ground light  
Perfect for both interior and exterior applications  
Compliments environments with ultra low glare up-lighting effect  
Marine-grade stainless steel 316 or Brass

Light source  
energy efficiency:



Beam angles: 12° 30°

