



GL019 LG

1W, 65lm mini low glare ground light

Features

IK Rating	IK07
IP Rating	IP68
CSP Switchable	Single CCT
UGR	10
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	33
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	204g
Ambient Temperature Range	50°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL019LGFW	Stainless steel 316	1W (350mA)	4000K	30°	65	65	262
GL019LGSNW	Stainless steel 316	1W (350mA)	4000K	12°	65	65	908
GL019LGFWW	Stainless steel 316	1W (350mA)	3000K	30°	55	55	222
GL019LGSWW	Stainless steel 316	1W (350mA)	3000K	12°	55	55	768
GL019LGF27	Stainless steel 316	1W (350mA)	2700K	30°	53	53	214
GL019LGS27	Stainless steel 316	1W (350mA)	2700K	12°	53	53	740

Energy rating is a reflection of the LED light source.

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 years

Features & benefits

- 1W at 350mA or 2W at 700mA
- Honeycomb baffle for low glare and visual comfort
- Low voltage ground light
- Compact yet powerful fitting
- Shallow depth for easy installation
- Robust cable for outdoor use
- Marine-grade stainless steel 316

Beam angles: 12° 30°

