



GL019 LG

1W, 65lm mini low glare ground light

Features

| | |
|------------------------|-------------|
| IK Rating | IK07 |
| IP Rating | IP68 |
| CSP Switchable | Single CCT |
| UGR | 10 |
| Walk Over / Drive Over | Walk over |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |

Installation information

| | |
|---------------------------|-----------------------|
| Cut Out Size | 33 |
| UK Bathroom Zone | 0 |
| Inrush Current | N/A |
| Construction Material | Stainless steel (316) |
| Weight | 204g |
| Ambient Temperature Range | 50°C |
| Electric Class (1, 2, 3) | 3 |

Photometrics @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | lx @ 1m |
|--------------|---------------------|----|--------|------|----|------|---------|
| GL019LGFNW | Stainless steel 316 | 1W | 4000K | 30° | 65 | 65 | 262 |
| GL019LGSNW | Stainless steel 316 | 1W | 4000K | 12° | 65 | 65 | 908 |
| GL019LGFWW | Stainless steel 316 | 1W | 3000K | 30° | 55 | 55 | 222 |
| GL019LGSWW | Stainless steel 316 | 1W | 3000K | 12° | 55 | 55 | 768 |
| GL019LGF27 | Stainless steel 316 | 1W | 2700K | 30° | 53 | 53 | 214 |
| GL019LGS27 | Stainless steel 316 | 1W | 2700K | 12° | 53 | 53 | 740 |

Wiring information

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |

LED drivers

| | | | | | | |
|-------------|----------|-----|----|---|---|---|
| PLU/350 1-9 | 220-240V | Yes | No | 0 | 1 | 9 |
| PLU/700 3-9 | 220-240V | Yes | No | 0 | 3 | 9 |
| PSIP70018W | 220-240V | Yes | No | 0 | 1 | 8 |

Accessories

| | | |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | IP68 waterproof connectors | Sold Separately |
| TUBE332 | Installation tube | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

7 years

Features & benefits

1W at 350mA or 2W at 700mA

Honeycomb baffle for low glare and visual comfort

Low voltage ground light

Compact yet powerful fitting

Shallow depth for easy installation

Robust cable for outdoor use

Marine-grade stainless steel 316

Light source
energy efficiency:



Beam angles: 12° 30°

