



## GL019 LG

1W, 65lm mini low glare ground light

### Features

<b>IK Rating</b>	IK07
<b>IP Rating</b>	IP68
<b>CSP Switchable</b>	Single CCT
<b>UGR</b>	10
<b>Walk Over / Drive Over</b>	Walk over
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3

### Installation information

<b>Cut Out Size</b>	33
<b>UK Bathroom Zone</b>	0
<b>Inrush Current</b>	N/A
<b>Construction Material</b>	Stainless steel (316)
<b>Weight</b>	204g
<b>Ambient Temperature Range</b>	50°C
<b>Electric Class (1, 2, 3)</b>	3

### Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL019LGFNW	Stainless steel 316	1W	4000K	30°	65	65	262
GL019LGSNW	Stainless steel 316	1W	4000K	12°	65	65	908
GL019LGFWW	Stainless steel 316	1W	3000K	30°	55	55	222
GL019LGSWW	Stainless steel 316	1W	3000K	12°	55	55	768
GL019LGF27	Stainless steel 316	1W	2700K	30°	53	53	214
GL019LGS27	Stainless steel 316	1W	2700K	12°	53	53	740

### Wiring information

<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series

### LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

### Accessories

<b>JB2 / JB4 / JB6</b>	IP68 waterproof connectors	Sold Separately
<b>TUBE332</b>	Installation tube	Sold Separately
<b>PDC/GRID DIMMER</b>	Grid dimmer kit for multiple fitting types	Sold Separately



collingwood

01604 495 151  
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

### Guarantee

7 years

### Features & benefits

1W at 350mA or 2W at 700mA

Honeycomb baffle for low glare and visual comfort

Low voltage ground light

Compact yet powerful fitting

Shallow depth for easy installation

Robust cable for outdoor use

Marine-grade stainless steel 316

Light source  
energy efficiency:



Beam angles: 12° 30°

