



## GL019 LG

1W, 65lm mini low glare ground light

### Features

IK Rating	IK07
IP Rating	IP68
CSP Switchable	Single CCT
UGR	10
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

### Installation information

Cut Out Size	33
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	204g
Ambient Temperature Range	50°C
Electric Class (1, 2, 3)	3

### Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL019LGFNW	Stainless steel 316	1W (350mA)	4000K	30°	65	65	262
GL019LGSNW	Stainless steel 316	1W (350mA)	4000K	12°	65	65	908
GL019LGFWW	Stainless steel 316	1W (350mA)	3000K	30°	55	55	222
GL019LGSWW	Stainless steel 316	1W (350mA)	3000K	12°	55	55	768
GL019LGF27	Stainless steel 316	1W (350mA)	2700K	30°	53	53	214
GL019LGS27	Stainless steel 316	1W (350mA)	2700K	12°	53	53	740

Energy rating is a reflection of the LED light source.

### Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

### LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

### Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



01604 495 151  
collingwoodlighting.com

collingwoodled  
 /collingwoodlighting  
 collingwoodlighting

### Guarantee

7 years

### Features & benefits

1W at 350mA or 2W at 700mA

Honeycomb baffle for low glare and visual comfort

Low voltage ground light

Compact yet powerful fitting

Shallow depth for easy installation

Robust cable for outdoor use

Marine-grade stainless steel 316

Light source  
energy efficiency:



Beam angles: 12° 30°

