



GL021

30° slotted LED ground / step light

Features

CSP Switchable	Single CCT
Walk Over / Drive Over	Walk over (Stainless Steel Only)
LED Lifetime	L70 70,000h

Installation information

Cut Out Size	50
UK Bathroom Zone	0
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	400g
SELV	N/A
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL021 NW	Stainless steel	1W	4000K	30°	10	10	10
GL021 WW	Stainless steel	1W	3000K	30°	8	8	8
GL021 27	Stainless steel	1W	2700K	30°	8	8	7

Energy rating is a reflection of the LED light source.

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A	N/A	N/A
PSIP3509W	220-240V	Yes	No	0	1	8
PSIP35018W	220-240V	Yes	No	1	N/A	N/A

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/50	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 years

Features & benefits

- 1W at 350mA
- Coastal protected
- Low voltage groundlight
- Angled light, ideal for use as a step light
- Robust cable for outdoor use
- Brushed stainless steel for sleek effect

Light source
energy efficiency:



Beam angles: C0/C180 C90/C270

