



GL038

2.9W, 300lm ground light

Features

IK Rating	IK08
IP Rating	IP65
CSP Switchable	Single CCT
Walk Over / Drive Over	Walk over
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Driver Rated Wattage	4W

Installation information

Cut Out Size	80-85
UK Bathroom Zone	2
Inrush Current	60A 0.037ms
Construction Material	Stainless steel 316 (top) / aluminium (body)
Weight	696g
Ambient Temperature Range	35°C
SELV	Yes
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL038DWBM27	Stainless steel 316	2.9W	2700K	40°	280	96	526
GL038DWBM30	Stainless steel 316	2.9W	3000K	40°	290	100	544
GL038DWBM40	Stainless steel 316	2.9W	4000K	40°	300	103	563
GL038AWBM27	Antique brass	2.9W	2700K	40°	280	96	526
GL038AWBM30	Antique brass	2.9W	3000K	40°	290	100	544

Energy rating is a reflection of the LED light source.

Wiring information

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED driver

N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A
------------------------------	----------	-----	----	---	-----	-----

Accessories

Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 years

Features & benefits

- 2.9W
- Coastal protected
- Mains voltage groundlight
- Single LED and lens combination for maximum efficiency and optimal light distribution
- Marine grade stainless steel 316 or antique brass
- Long lifetime of 70,000hrs