



# GL045

8W, 610lm walk over ground light

## Features

IK Rating	IK08
IP Rating	IP67
CSP Switchable	Single CCT
Tiltable	No
UGR	10
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6

## Installation information

Cut Out Size	120
UK Bathroom Zone	2
Inrush Current	20A 0.5ms
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
Weight	917g
Ambient Temperature Range	40°C
SELV	Yes
Electric Class (1, 2, 3)	1

## Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
GL045X30	Stainless steel	8.1W	3000K	20°	610	75	2924

Energy rating is a reflection of the LED light source.

## Wiring information

Cable / Flying Lead	160mm H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

## LED driver

N/A (integrated SELV driver)	220-240V	Yes	N/A	2	N/A	N/A
------------------------------	----------	-----	-----	---	-----	-----

## Accessories

JB5	IP68 waterproof connector	Sold Separately
WCR375BLACK	3-core rubber cable	Sold Separately
Installation Tube	Diameter: 120mm, Depth: 105mm	Included



01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

5 years

## Features & benefits

- 8W
- Coastal protected
- Mains voltage ground light
- 120mm cut out diameter
- A narrow beam angle of 20° for a more focused light
- High impact rating of IK08
- High light output of 610 lumens
- Low glare UGR <10