



# GL063

3W, 45lm 3 way ground light

## Features

IK Rating	IK10
IP Rating	IP67
CSP Switchable	Single CCT
Walk Over / Drive Over	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

## Installation information

Cut Out Size	55
UK Bathroom Zone	1
Inrush Current	N/A
Construction Material	Cast stainless steel (316)
Weight	1.165Kg
Ambient Temperature Range	35°C
Electric Class (1, 2, 3)	3

## Photometrics @ 25°C

Product code	Finish	W	Colour	lm	lm/W	lx @ 1m
GL063	Stainless steel	3W	3000K	45	15	9

## Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

## LED drivers

PLU/350 1-9	220-240V	Yes	No	0	1	3
PSIP3509W	220-240V	Yes	No	0	1	2
PSMD35039	220-240V	Yes	Yes (mains)	0	1	3

## Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

7 years

## Features & benefits

- 3W at 350mA
- Coastal protected
- Low voltage ground light
- Cast stainless steel for aged effect
- Raised profile sending light in three directions

Beam angles: **C0/C180** **C90/C270**

