





01604 495 151  
collingwoodlighting.com

 collingwoodled

 /collingwoodlighting

 collingwoodlighting

# GL090RGBW

High output LED colour change ground light (12W max.)

## Features

IK Rating	IK08
IP Rating	IP67
CSP Switchable	RGBW
Walk Over / Drive Over	Walk over
LED Lifetime	L50 50,000h

## Installation information

Cut Out Size	70
UK Bathroom Zone	1
Construction Material	Stainless steel (316)
Weight	900g
Ambient Temperature Range	35°C
Electric Class (1, 2, 3)	3

## Wiring information

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series

## LED drivers

CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	N/A	4
CCDRV75DMX	220-240V	Yes	Yes	2	N/A	4
CCDRV75RF	220-240V	Yes	Yes	2	N/A	4

## Accessories

TUBE/68	Installation tube	Sold Separately
JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately

## PRODUCT CODES

Colour / Finish	Short Description
GL090RGBW	High output LED colour change ground light (12W max.)

## Guarantee

5 years

## Features & benefits

RGBW

Coastal protected

IK08 suitable for pathways

High output colour change for large areas

Marine grade stainless steel for use in outdoor and indoor environments


Separate white LED for permanent use

Compatible with a large range of controllers

Light source energy efficiency:



Beam angle: 45°



Ø75mm

