



# Tilt Adjustable Ground Light

Straight to Mains, DALI-2 dimmable

## Features

IK Rating	IK08
IP Rating	IP67
CSP Switchable	Single CCT
Tilttable	25°
Walk Over / Drive Over	Drive over (15mph maximum)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

## Installation information

Cut Out Size	147
UK Bathroom Zone	2
Inrush Current	GLTM_14: 0.55A 0.14ms, GLTM_16: 0.45A 0.5ms, GLTM_19: 0.025ms, GLTM_22: 0.5A 0.3ms
Construction Material	Anodised aluminium body, 316 SS bezel
Weight	GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg, GLTM_22: 3.98kg
Ambient Temperature Range	-25°C - 40°C
Electric Class (1, 2, 3)	1

## Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	W	Colour	Beam	lm	lm/W
GLTMS147D30	Stainless steel 316	147mm cut-out	IK08	10W	3000K	34°	1000	100
GLTMS165D30	Stainless steel 316	165mm cut-out	IK10	18W	3000K	34°	1600	89
GLTMS193D30	Stainless steel 316	193mm cut-out	IK10	23W	3000K	34°	2300	100
GLTMS223D30	Stainless steel 316	223mm cut-out	IK10	28W	3000K	34°	3300	100

Energy rating is a reflection of the LED light source.

## Wiring information

Cable / Flying Lead	Pre-wired 1.0M H05RN-F, 3x1.0mm2
Type of Wiring Required	Parallel

## Accessories

DM298FP	Faceplate rotary mains dimmer	Sold Separately
DM298GRID	Grid rotary mains dimmer	Sold Separately
JB5	Gel filled waterproof connector	Sold Separately



01604 495 151  
collingwoodlighting.com

collingwoodled  
 /collingwoodlighting  
 collingwoodlighting

## Guarantee

5 years

## Features & benefits

IP67 for complete protection against ingress of dust & water

IK08 (GLTM\_11/14) IK10 (GLTM\_16/19/22)

Suitable for coastal applications

Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees

Static loading capacity is 2000kg

Pre-wired with 1 meter of cable to aid the installer

TRIAC mains dimmable and RGBW options also available

Supplied with installation tube

Light source energy efficiency:



Beam angle: 34°

