



Tilt Adjustable Ground Light

Straight to Mains, DALI-2 dimmable

Features

| | |
|------------------------|----------------------------|
| IK Rating | IK08 |
| IP Rating | IP67 |
| CSP Switchable | Single CCT |
| Tiltable | 25° |
| Walk Over / Drive Over | Drive over (15mph maximum) |
| LED Lifetime | L70 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |

Installation information

| | |
|---------------------------|--|
| Cut Out Size | 147 |
| UK Bathroom Zone | 2 |
| Inrush Current | GLTM_14: 0.55A 0.14ms, GLTM_16: 0.45A 0.5ms, GLTM_19: 0.025ms, GLTM_22: 0.5A 0.3ms |
| Construction Material | Anodised aluminium body, 316 SS bezel |
| Weight | GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg, GLTM_22: 3.98kg |
| Ambient Temperature Range | -25°C - 40°C |
| Electric Class (1, 2, 3) | 1 |

Photometrics @ 25°C

| Product code | Finish | Feature I | Feature II | W | Colour | Beam | lm | lm/W |
|--------------|---------------------|---------------|------------|-----|--------|------|------|------|
| GLTMS147D30 | Stainless steel 316 | 147mm cut-out | IK08 | 10W | 3000K | 34° | 1000 | 100 |
| GLTMS165D30 | Stainless steel 316 | 165mm cut-out | IK10 | 18W | 3000K | 34° | 1600 | 89 |
| GLTMS193D30 | Stainless steel 316 | 193mm cut-out | IK10 | 23W | 3000K | 34° | 2300 | 100 |
| GLTMS223D30 | Stainless steel 316 | 223mm cut-out | IK10 | 28W | 3000K | 34° | 3300 | 100 |

Wiring information

| | |
|-------------------------|--|
| Cable / Flying Lead | Pre-wired 1.0M H05RN-F, 3x1.0mm ² |
| Type of Wiring Required | Parallel |

Accessories

| | | |
|-----------|---------------------------------|-----------------|
| DM298FP | Faceplate rotary mains dimmer | Sold Separately |
| DM298GRID | Grid rotary mains dimmer | Sold Separately |
| JB5 | Gel filled waterproof connector | Sold Separately |



01604 495 151
collingwoodlighting.com

collingwoodled
 /collingwoodlighting
 collingwoodlighting

Guarantee

5 years

Features & benefits

IP67 for complete protection against ingress of dust & water

IK08 (GLTM_11/14) IK10 (GLTM_16/19/22)

Suitable for coastal applications

Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees

Static loading capacity is 2000kg

Pre-wired with 1 meter of cable to aid the installer

TRIAC mains dimmable and RGBW options also available

Light source energy efficiency:



Beam angle: 34°

