



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Springbok Lite 11,000lm

80W High bay luminaire (Replaces 150W or 2x80W T5)

Features

| | |
|------------------------|---------------------------------------|
| IK Rating | IK08 |
| IP Rating | IP65 |
| CSP Switchable | Single CCT |
| Sensor Option | Microwave & Daylight with accessories |
| Dimmable Option | No |
| LED Lifetime | L70 54,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM5 |
| Emergency Option | Yes, Manual-Test |

Installation information

| | |
|---------------------------|--------------------------------------|
| Install Connector Type | Flying lead |
| Inrush Current | 100A 0.42ms |
| Construction Material | ADC12 aluminium alloy tempered glass |
| Weight | 1.60kg |
| Ambient Temperature Range | -20°C - 40°C |
| UK Building Regulations | Part P |
| Electric Class (1, 2, 3) | 1 |

Photometrics @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | EM |
|--------------|--------------------|-----|--------|------|-------|------|-----|
| HBLIN | Matt black RAL9017 | 80W | 4000K | 110° | 11000 | 138 | 530 |
| HBLINEM | Matt black RAL9017 | 80W | 4000K | 110° | 11000 | 138 | 530 |

Energy rating is a reflection of the LED light source.

Wiring information

| | |
|-------------------------|--|
| Cable / Flying Lead | 1.5m H05RN-F 3x1.0mm ² Ø7mm |
| Type of Wiring Required | Parallel |

Accessories

| | | |
|----------|---|-----------------|
| HBLMWS | High Bay Sbok Lite, Microwave sensor kit inc junction box and counterweight | Sold Separately |
| HBREM | High Bay Sbok Lite, Remote control for commissioning HBLMWS | Sold Separately |
| HBL1REFR | High Bay Sbok Lite, 80W 80-degree refractor | Sold Separately |
| HBBRA | Bracket Mount for Standard Springbok Lite | Sold Separately |
| HBBRAEXT | Extended Bracket Mount for Standard Springbok Lite | Sold Separately |

Guarantee

4 years (product), 2 years (battery), 2 years (on-site)

Features & benefits

- High efficacy of 138lm/W
- Sensor kit includes junction box and counter weight
- Emergency option available
- Economical high bay for fast return on investment
- Easy to add microwave sensor kit includes junction box and counter weight
- On/off control with time delay and daylight switching (8-15 metres max)
- Suitable for jack chain, M10 drop rod or catenary wire suspension
- Pre-wired with 1.5M of H05RN-F cable for ease and speed of installation
- Replaceable driver for easy maintenance
- IK08 for robust impact protection

Light source energy efficiency:



Beam angle: 110°

