



LED LYTE

Mini LED light

Features

IP Rating	IP30
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	26
UK Bathroom Zone	N/A
Inrush Current	N/A
Construction Material	Plastic
Weight	20g
Ambient Temperature Range	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
LED LYTE NW	Chrome	1W	4000K	110°	82	82	46
LED LYTE WW	Chrome	1W	3000K	110°	60	60	30
LED LYTE 27	Chrome	1W	2700K	110°	58	58	29
LED LYTE RED	Chrome	1W	Red	110°	-	-	-

Wiring information

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series

LED drivers

PLU/PP/350 1-9 (Plug & Play)	220-240V	Yes	No	Outside zones	1	9
PSIP3509W	220-240V	Yes	No	Outside zones	1	8
PSMD35039	220-240V	Yes	Yes (mains)	Outside zones	3	9

Accessories

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

7 years

Features & benefits

Quick and easy installation with plug and play connector

Coastal protected

IP30 perfect for interior applications

Mini LED perfect for small room e.g. closets

Small & discreet

Light source energy efficiency:



Beam angle: 110°

