



LEDEP09DA

DALI Self-test emergency converter pack

Features

IP Rating	IP20
-----------	------

Installation information

Install Connector Type	Mains: Push-fit terminals 0.75 - 1.5mm ² DC: Plug & Play connectors
Insulation Coverable	No
Double Insulation	Yes
Cut Out Size	55mm
Inrush Current	4A 0.55ms
Construction Material	Polycarbonate
Weight	378g
Ambient Temperature Range	5°C - 35°C
SELV	Yes
Electric Class (1, 2, 3)	2

Wiring information

Cable / Flying Lead	2x 1mm ² H05VV-F
Type of Wiring Required	Parallel

Accessories

N/A	No accessories are required
-----	-----------------------------

PRODUCT CODES

	Colour / Finish	Description	Characteristic 1
LEDEP09DA	White	DALI Self-test emergency converter pack	LiFePO ₄ Battery



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years (electronics), 3 years (battery)

Features & benefits

- Self-test device, simple emergency lighting inspections
- DALI compatible
- Design allows installation through ceiling cut out of 55mm
- Dual colour Green / Red LED status indicator
- Lithium iron phosphate (LiFePO₄) battery
- Supplied with a test button, whereby a battery duration test can be carried out at anytime
- Synchronizes an automatic battery duration test every 6 months
- 3-pole isolation of lamp & mains driver power during emergency
- Battery connectors are polarity protected

