

## Uplights (Façade lights) specification sheet



# Volta 1000mm

Wall washing light bar

## Features

IK Rating	IK04
IP Rating	IP65
CSP Switchable	Single CCT
Dimmable Option	Yes (Mains)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

## Installation information

UK Bathroom Zone	1
Inrush Current	15A 10s
Construction Material	Anodised aluminium
Weight	2.5kg
Ambient Temperature Range	50°C
SELV	Yes
Electric Class (1, 2, 3)	2

## Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
LL1000MT30	Silver	40W	3000K	30°	4200	105	10745
LL1000WT30	Silver	40W	3000K	60°	4200	105	4251
LL1000AT30	Silver	40W	3000K	20x35°	4200	105	10860
LL1000MT27	Silver	40W	2700K	30°	4200	105	10745
LL1000WT27	Silver	40W	2700K	60°	4200	105	4251
LL1000AT27	Silver	40W	2700K	20x35°	4200	105	10860

## Wiring information

Cable / Flying Lead	0.8m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

## LED driver

N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A	N/A	N/A
------------------------------	----------	-----	-----	-----	-----	-----

## Accessories

N/A	No accessories required
-----	-------------------------



collingwood

01604 495 151  
collingwoodlighting.com

collingwoodled  
/collingwoodlighting  
collingwoodlighting

## Guarantee

7 years

## Features & benefits

40W  
IP65 ideal for outdoor environments  
Suitable for use in coastal applications  
Plug and play through-wire install method  
Supplied with waterproof connectors for fast install  
3000K and 2700K range with choice of 2000 or 4200 lumen output  
Narrow beam 30°, Wide beam 60° or Asymmetrical 20x35°  
Also available in 500mm

Light source energy efficiency:



Beam angle: 30°, 60°, 20x35°

