

# Salvus PIR Bolt-On

On/Off PIR sensor with Lux level switch

## Features

IK Rating	IK07
IP Rating	IP65
Sensor Option	PIR

## Installation information

Install Connector Type	Flying lead
UK Bathroom Zone	N/A
Construction Material	PC
Weight	82g
Electric Class (1, 2, 3)	2

## USE WITH

Borealis Batten	PIRBOLTDIM requires a 0-10V dimmable driver, PIRBOLT can be used with any driver	Sold Separately
Caiman Anti Corrosive	PIRBOLTDIM requires a 0-10V dimmable driver, PIRBOLT can be used with any driver	Sold Separately

## PRODUCT CODES

	Colour / Finish	Description	Characteristic 1	Characteristic 2	Characteristic 3
PIRBOLT	White RAL9016	On/Off PIR sensor with Lux level switch 3-300 lx	On-Off	Commissioned using dials on sensor	3-300lx daylight switch
PIRBOLT DIM	White RAL9016	Dimming PIR Sensor with Lux Level switch 0-2000lx	Step Dim	Commissioned using remote	3-2000lx daylight switch
PIRBOLT DIMR		Remote control for use with PIRBOLTDIM		*Sold Separately*	



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

5 Years

## Features & benefits

Compatible with: BOREALIS, CAIMAN Anti-Corrosive, LENTUS

Suitable for use at heights of 2.5 to 6.0 metres


Quick and easy installation with M20 interface

Fast 4-minute conversion time

PIRBOLTDIM requires the luminaire to have a 0-10V driver

PIRBOLTDIMR - CR2025 battery not included

## Beam angle:



136mm

