



Qubo

Architectural projector feature light for indoor and outdoor applications

Features

IK Rating	IK08
IP Rating	IP66
CSP Switchable	Single CCT
Tiltable	120°
Rotation Angle	60°
Sensor Option	PC Dusk to Dawn
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6

Installation information

Inrush Current	QBAL: 12A 0.156ms, QBAM: 3.5A 0.14ms
Construction Material	Aluminium Housing, PMMA Diffuser, Grade 304 Screws
Weight	QBAL: 1700g, QBAM: 700g
Ambient Temperature Range	-20°C - 30°C
SELV	Yes
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	Feature I	W	Colour	Beam	lm	lm/W	lx @ 1m
QBAMN30	Anthracite grey RAL7016	Medium	10W	3000K	30°	1000	100	2141
QBALN30	Anthracite grey RAL7016	Large	18W	3000K	30°	2000	111	4402

Wiring information

Cable / Flying Lead	2m Neoprene H05RN-F 3x0.75mm2 cable supplied
Type of Wiring Required	Parallel

LED driver

N/A (integrated driver)	N/A	N/A	N/A	N/A	N/A	N/A
-------------------------	-----	-----	-----	-----	-----	-----

Accessories

N/A	No accessories required
-----	-------------------------



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years

Features & benefits

- IP66 ideal for internal or external applications
- High lumen output of up to 2000lm
- Robust impact rating of IK08
- Outdoor LED projector with bracket and spike for installation on floor or ground
- Adjustable, rotation 0-60°, 0-120° tilt
- Precision tilting degree marker on the product to facilitate orientation
- Neoprene H05RN-F 2x0.75mm2 cable of 2000mm

Light source energy efficiency:



Beam angle: 30°

