



SL240 Mains

Mains voltage LED twin bar spike light

Features

IP Rating	IP65
CSP Switchable	Single CCT
Tilttable	90°
Rotation Angle	330°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

UK Bathroom Zone	N/A
Inrush Current	120A 375s
Construction Material	Anodised aluminium Stainless Steel 316
Weight	SL240B: 1584g SL240D: 2700g SL240Z: 1414g
Ambient Temperature Range	35°C
SELV	SELV
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
SL240ZWBM27	Bronze anodised aluminium	11.4W	2700K	40°	1030	2 x 90	2 x 1171
SL240ZWBM30	Bronze anodised aluminium	11.4W	3000K	40°	1040	2 x 91	2 x 1182
SL240BWBM27	Black anodised aluminium	11.4W	2700K	40°	1030	2 x 90	2 x 1171
SL240BWBM30	Black anodised aluminium	11.4W	3000K	40°	1040	2 x 91	2 x 1182
SL240DWB30	Stainless steel	11.4W	3000K	40°	1040	2 x 91	2 x 1182

Wiring information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED driver

N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A
------------------------------	----------	-----	----	-----	-----	-----

Accessories

JB5	Gel filled waterproof connector	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 years

Features & benefits

- 11.4W
- Coastal protected
- IP65 ideal for outdoor areas
- Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features
- Easily ground mounted with two spikes and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Mains voltage for easy installation
- Highly efficiency of 93lm/W

Light source energy efficiency:



Beam angle: 40°

