



# SL250

Low voltage, 24V, LED path light with spike

## Features

IP Rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6

## Installation information

UK Bathroom Zone	N/A
Inrush Current	N/A
Construction Material	Brass, powder coated aluminium
Weight	Black: 1374g, Brass: 1390g
Ambient Temperature Range	35°C
Electric Class (1, 2, 3)	3

## Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
SL250ATX0X27	Brass, treated	6W	2700K	60-110°	200	50	152 / 68
SL250ATX0X30	Brass, treated	6W	3000K	60-110°	220	55	167 / 75
SL250BPX0X27	Black powder coated aluminium	6W	2700K	60-110°	200	50	152 / 68
SL250BPX0X30	Black powder coated aluminium	6W	3000K	60-110°	220	55	167 / 75

## Wiring information

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Parallel

## LED drivers

PS3024B	220-240V	Yes	No	0	1	5
LSD6024	220-240V	Yes	No	0	1	9
PS7524	220-240V	Yes	N/A	0	1	12

## Accessories

JB1 / JB5 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
SL250A1	Surface mounted base plate	Sold Separately



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

7 years

## Features & benefits

- 6W at 24V
- IP65 ideal for outdoor areas
- Low voltage product
- Robust cable for outdoor use
- Long lifetime of 50,000hrs
- 7 year warranty
- Note product is non-dimmable

