



UL010

Universal LED light

Features

IP Rating	IP68
CSP Switchable	Single CCT
Tilttable	360°
Rotation Angle	360°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Inrush Current	N/A
Construction Material	Stainless steel (316), brass, anodised aluminium
Weight	500g
Ambient Temperature Range	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
UL010 NW	Stainless steel 316	3W	4000K	26°	119	40	648
UL010 WW	Stainless steel 316	3W	3000K	26°	95	32	411
UL010 27	Stainless steel 316	3W	2700K	26°	92	31	399
UL010 A WW	Brass	3W	3000K	26°	95	32	411
UL010 A 27	Brass	3W	2700K	26°	92	31	399
UL010 B 30	Black anodised aluminium	3W	3000K	26°	95	32	411
UL010 B 27	Black anodised aluminium	3W	2700K	26°	92	31	399

Wiring information

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8
PSDIM700	220-240V	N/A	Yes (1-10V)	0	1	18

Accessories

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



01604 495 151
collingwoodlighting.com

collingwoodled
 /collingwoodlighting
 collingwoodlighting

Guarantee

7 years

Features & benefits

3W at 700mA
Coastal protected
IP68 ideal for outdoor areas and under water lighting
Complete with wall fixings
Robust cable for use outdoors
Tilt & rotate for adjusting light
Long lifetime of 70,000hrs

Light source
energy efficiency:



Beam angle: 26°

