



UL010RGBW

Colour change LED light (5W max.)

Features

IP Rating	IP67
CSP Switchable	RGBW
Tilttable	360°
Rotation Angle	360°
Dimmable Option	Driver dependent
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80

Installation information

UK Bathroom Zone	1
Construction Material	Stainless steel (316)
Weight	700g
Ambient Temperature Range	35°C
Electric Class (1, 2, 3)	3

Wiring information

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series

LED drivers

CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	N/A	13
CCDRV75DMX	220-240V	Yes	Yes	2	N/A	13
CCDRV75RF	220-240V	Yes	Yes	2	N/A	13

Accessories

JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
CCRFCONVWIFI / CCREMOTE / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately

PRODUCT CODES

Colour / Finish	Short Description
UL010RGBW	Colour change LED light (5W max.)



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

5 years

Features & benefits

RGBW

Coastal protected

IP67 ideal for outdoor areas and under water lighting

Complete with wall fixings for easy installation

Can rotate and be angled to direct light

Separate white LED for permanent use

Compatible with a large range of controllers

Marine grade stainless steel for use in outdoor and indoor environments

Light source
energy efficiency:



Beam angle: 40°

