



# Uniform 6ft

1800mm Surface Linear

## Features

<b>IK Rating</b>	IK08
<b>IP Rating</b>	IP44 (ceiling surface mount) IP40 (suspended or wall mounted)
<b>CSP Switchable</b>	Single CCT
<b>UGR</b>	22
<b>Sensor Option</b>	Bolt-On PIR
<b>Dimmable Option</b>	Yes (DALI-2, PUSH-DIM)
<b>LED Lifetime</b>	L80 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Emergency Option</b>	Yes, Self-Test

## Installation information

<b>Install Connector Type</b>	Push-fit terminal, loop-in/loop-out
<b>Inrush Current</b>	15.4A 0.48ms
<b>Construction Material</b>	Carbon Sheet Steel Housing, Polycarbonate Diffuser
<b>Weight</b>	4.6kg
<b>Ambient Temperature Range</b>	-20°C - 40°C
<b>Electric Class (1, 2, 3)</b>	1

## Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	W	Colour	Beam	lm	lm/W	EM
UNL6SN	White RAL9016	Non-Dimmable with Wattage Output Switch	-	20W - 23W - 26W - 30W	4000K	120°	2822 3383 3984 4500	150 - 150 - 150 - 150	-
UNL6SNE	White RAL9016	Non-Dimmable with Wattage Output Switch	Emergency	20W - 23W - 26W - 30W	4000K	120°	2822 3383 3984 4500	150 - 150 - 150 - 150	325
UNL6SD	White RAL9016	DALI-2 Dimmable	-	30W	4000K	120°	4500	150	-
UNL6SDE	White RAL9016	DALI-2 Dimmable	Emergency	30W	4000K	120°	4500	150	325

## Wiring information

<b>Cable Required for Connector</b>	Mains Cable
<b>Type of Wiring Required</b>	Parallel

## Accessories

<b>PIRBOLT</b>	On-off PIR sensor with daylight switch	Sold Separately
<b>EMBOLTMOPEN</b>	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
<b>EMBOLTCOR</b>	Bolt-on emg conversion pack, Man-Test, 200lm	Sold Separately
<b>EMBOLTSOPEN</b>	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately
<b>EMBOLTSCOR</b>	Bolt-on emg conversion pack, Self-Test, 200lm	Sold Separately



collingwood

01604 495 151  
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

## Guarantee

5 years (product), 3 years (emerg battery)

## Features & benefits

Wattage switchable between 20W, 23W, 26W & 30W

Ultra-efficient up to 150 lm/W

Quick and easy installation with Push-fit terminal

Outstanding uniform lit effect

70,000 hours L80 lifetime


IP44 rated allows the product to be used in a wide range of applications

Bolt-on range of lighting controls and emergency conversion packs to aid fast availability

RG0 (Risk Exempt) Photo-biological Risk

Suspension kit available (UNLSUS2M)

Light source energy efficiency:



Beam angle: 120°

