


## Wall lights specification sheet



# WL012

IP54, 610lm straight to mains wall light

## Features

IK Rating	IK04
IP Rating	IP54
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5

## Installation information

UK Bathroom Zone	N/A
Inrush Current	20A 0.5ms
Construction Material	Powder coated aluminium
Weight	1kg
Ambient Temperature Range	40°C
SELV	SELV
Electric Class (1, 2, 3)	1

## Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
WL012X30	Black RAL9011	11.0W	3000K	338°	610	55	72
WL012G30	Grey RAL7022	11.0W	3000K	338°	610	55	72

## Wiring information

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

## Accessories

N/A	No accessories required
-----	-------------------------



01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

5 years

## Features & benefits

11W

Integral bracket for easy installation

IP54 ideal for framing doorways and entrances

Straight to mains screw terminals

Durable powder coated aluminium in contemporary black or grey finish

Provides a good light level for safe navigation at night

Wide light distribution with 360° beam angle

Light source  
energy efficiency:



Beam angle: 338°

