



WL012

IP54, 610lm straight to mains wall light

Features

| | |
|------------------------|-------------|
| IK Rating | IK04 |
| IP Rating | IP54 |
| CSP Switchable | Single CCT |
| Dimmable Option | No |
| LED Lifetime | L70 30,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM5 |

Installation information

| | |
|---------------------------|-------------------------|
| UK Bathroom Zone | N/A |
| Inrush Current | 20A 0.5ms |
| Construction Material | Powder coated aluminium |
| Weight | 1kg |
| Ambient Temperature Range | 40°C |
| SELV | SELV |
| Electric Class (1, 2, 3) | 1 |

Photometrics @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | lx @ 1m |
|--------------|---------------|-------|--------|------|-----|------|---------|
| WL012X30 | Black RAL9011 | 11.0W | 3000K | 338° | 610 | 55 | 72 |
| WL012G30 | Grey RAL7022 | 11.0W | 3000K | 338° | 610 | 55 | 72 |

Wiring information

| | |
|-------------------------|----------|
| Cable / Flying Lead | N/A |
| Type of Wiring Required | Parallel |

Accessories

| | |
|-----|-------------------------|
| N/A | No accessories required |
|-----|-------------------------|



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years

Features & benefits

- 11W
- Integral bracket for easy installation
- IP54 ideal for framing doorways and entrances
- Straight to mains screw terminals
- Durable powder coated aluminium in contemporary black or grey finish
- Provides a good light level for safe navigation at night
- Wide light distribution with 360° beam angle

Light source
energy efficiency:



Beam angle: 338°

